



Rozpora rolkowa

Nazwa	Długość rozpory rolkowej L_{RR} [m]	Szerokość rozpory rolkowej B_{RR} [m]	Min. światło wykopu b_c [m]	Kołnierz $b_K \times h_K$ [mm]	Masa pary rozpór rolkowych [kg]
MINI RR	1,24	0,62	1,24	405 x 420	620
STANDARD RR	2,04	0,62	1,24	405 x 720	980
MAX RR	3,04	0,92	1,83	405 x 1220	1 700
NADSTAWKA RR	1,24	0,62	1,24	405 x 420	620

Wstawka do rozpory rolkowej

Nazwa	Długość W [m]	Mini RR		Standard RR		Max RR	
		[mm]	[kg]	[mm]	[kg]	[mm]	[kg]
W 250	0,25	405 x 420	99	405 x 720	163	405 x 1 220	306
W 500	0,50	405 x 420	128	405 x 720	201	405 x 1 220	363
W 750	0,75	405 x 420	157	405 x 720	239	405 x 1 220	418
W 1000	1,00	405 x 420	185	405 x 720	277	405 x 1 220	474
W 2000	2,00	405 x 420	303	405 x 720	437	405 x 1 220	714
W 3000	3,00	405 x 420	421	405 x 720	597	405 x 1 220	960